

PMC MATT LAMI PP29C WG62

**Country of
manufacture:** Thailand

Applications: Matt clear biaxially oriented polypropylene film designed for over laminating that provides increased abrasion and splash resistance. It also gives an elegant matt finish to paper and other relative base labels.

Product components

**Face
(MATT LAMI):** Matt transparent BOPP film non-top coated biaxially oriented PP film.

Adhesive (PP29C): General-purpose acrylic permanent adhesive with excellent clarity and aging resistance. Featuring good tack to low surface energy substrates.

Liner (WG62): Super calendered White Glassine paper

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	18gsm	20 micron (0,8 mil)
Liner	60gsm	55 micron (2,2 mil)
Total	97gsm, $\pm 10\%$	88 micron, $\pm 10\%$

ADHESIVE

Property			
Initial Tack	Glass	FTM 9	$\geq 9,5$ N/25 mm
Initial Tack	Stainless Steel	FTM 9	$\geq 9,0$ N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	$\geq 4,5$ N/25 mm
Minimum Service Temperature		-20 °C	-4 °F
Maximum Service Temperature		80 °C	176 °F
Minimum Application Temperature		-5 °C	23 °F

CERTIFICATES

- US FDA 21 CFR 175.105 (Adhesive) for indirect food contact packaging and processing.
- European Toy Safety Legislation 88/278/EEC, CEN EN71, Part 3

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 2 years if store in 22°C and RH 50% condition. The product must be stored in shady or cool place and do not expose to sunlight directly.

These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

