

PMC PREMIUM GLOSS BLOCKOUT PBK65F WG62

Country of manufacture: Thailand

Applications: Designed for wide range of labels and stickers, with a glossy finish, for general-purpose application. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

Product components

Face (Premium Gloss Blockout): Super white with glossy surface, one side cast coated, and mirror finished printing paper.

Adhesive (PBK65F): A general-purpose grey colour, permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.

Liner (WG62): Super calendared White Glassine paper.

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	80gsm	82 micron (3,2 mil)
Liner	60gsm	54 micron (2,1 mil)
Total	159 gsm, $\pm 10\%$	153 micron, $\pm 10\%$

ADHESIVE

Property

Initial Tack	Glass	FTM 9	≥ 12,5	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12,0	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6,5	N/25 mm
Minimum Service Temperature		-40 °C	-40 °F	
Maximum Service Temperature		120 °C	248 °F	
Minimum Application Temperature		-5 °C	23 °F	

CERTIFICATES

- US FDA 21 CFR 175. 105 (Adhesive) for indirect food contact packaging and processing.
-

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 1 year in 22°C and RH 50%. These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

