

PMC FLUORO YELLOW PP33F WG62

Country of manufacture:	Thailand
--------------------------------	----------

Applications:	General-purpose label designed for eye-catching applications such as instructional, promotional and POS label. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.
----------------------	---

Product components

Face (FLUORO YELLOW):	One sided fluorescent coloured coated paper.
-----------------------	--

Adhesive (PP33F):	General-purpose permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.
-------------------	---

Liner (WG62):	Super calendared White Glassine paper.
---------------	--

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	72gsm	80 micron (3,1 mil)
Liner	60gsm	54 micron (2,1 mil)
Total	153 gsm, $\pm 10\%$	154 micron, $\pm 10\%$

ADHESIVE

Property				
Initial Tack	Glass	FTM 9	$\geq 12,5$	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	$\geq 6,5$	N/25 mm
Minimum Service Temperature		-40 °C	-40 °F	
Maximum Service Temperature		120 °C	248 °F	
Minimum Application Temperature		-5 °C	23 °F	

CERTIFICATES

- US FDA 21 CFR 175.105 (Adhesive) for indirect food contact packaging and processing.
- European Toy Safety Legislation 88/278/EEC, CEN EN71, Part 3

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 1 year in 22°C and RH 50%. These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

