

PMC GLOSS 90 PP30F WG62

Country of manufacture: Thailand

Applications: Designed for high quality multicolor labels and stickers with high flexibility conformity requirements. It is advisable to test the product with end-use conditions during the qualification to ensure it meets specific requirements.

Product components

Face (GLOSS): White, glossy coated super calendered wood free printing paper. Recommend to varnish or over clear BOPP lamination if higher gloss level needed.

Adhesive (PP30F): General-purpose permanent adhesive. Featuring good tack to low surface energy.

Liner (WG62): Super calendered white glassine paper.

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Face	90gsm	73 micron (2.9 mil)
Liner	58gsm	51 micron (2 mil)
Total	169 gsm, $\pm 10\%$	144 micron, $\pm 10\%$



ADHESIVE

Property

Initial Tack	Glass	FTM 9	≥ 11	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 10,5	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 5	N/25 mm
Adhesion to	Corrugated paper	FTM 2 20 minute 90° peel	≥3,5	N/25 mm

LINER

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

CERTIFICATES

- US FDA 21 CFR 175.105 (Adhesive) for indirect food contact packaging and processing.

B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

Shelf Life: From the date of manufacture 1 year in 22°C and RH 50%. These characteristics are average values supplied for guidance purposes.

Note: It is the user's responsibility to test all stock, prior to use, whether the product is suitable for intended application.

