



## TECHNICAL SPECIFICATION SHEET

Updated: March 2017

### PRODUCT

---

## ADESTOR HI GLOSS 80 REMOVABLE RA678 WG62

### CATEGORY

---

Utility

### MANUFACTURER

---

Lecta

### WEBSITE

---

[www.adestor.com](http://www.adestor.com)

### COUNTRY OF MANUFACTURE

---

Barcelona

### APPLICATIONS

---

High resolution standard gloss label for multicolour printing. Extensively used in the food and beverage industry, logistics, stationery and cosmetic products.

### PRODUCT COMPONENTS

---

**Facestock (HI GLOSS 80):** Gloss coated wood free paper.

**Adhesive (RA678):** Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces.

**Liner (WG62):** Super-calendered white translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

### PRINTING TECHNIQUES

---

Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

**Please note:** B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

*B&F Papers are committed to being an environmentally responsible company. [www.bfpapers.co.nz](http://www.bfpapers.co.nz)*



## TECHNICAL SPECIFICATIONS

### FACESTOCK

Property	Units	Value	Tolerance
Substance	g/m <sup>2</sup>	90	±4%
Thickness	μm	78	±4
Bekk smoothness	s	≥700	
Brightness ISO	%	93	±2
Whiteness CIE	%	117	±3
Opacity	%	90	-2
Paper gloss 20°	%	66	±5
Tensile strength MD/CD	kN/M	5.2	-0.5

### ADHESIVE

Property	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	N/25mm	1.7	1-2.9
Shear (1kg, in <sup>2</sup> /glass)	Min	120	≥60
Tack (Quick Stick stainless steel)	N	1.2	0.7-1.7
Minimum labelling temperature	°C	5	
Minimum service temperature	°C	-20	
Maximum service temperature	°C	+80	

### LINER

Property	Units	Value	Tolerance
Substance	g/m <sup>2</sup>	62	59-65
Thickness	μm	52	49-55

Shelf life: From the date of manufacture 1 year in 20°C and RH 50%  
 These characteristics are average values supplied for guidance purposes.

**Note:** It is recommended that all pressure sensitive materials are trialled prior to printing.

**Please note:** B&F Papers has endeavoured to ensure this information is correct; however, we do not accept liability for any error or omission.

We reserve the right to update this information without prior notice.

*B&F Papers are committed to being an environmentally responsible company. [www.bfpapers.co.nz](http://www.bfpapers.co.nz)*