

PRODUCT

ADESTOR LASER 70 REMOVABLE RA678 KL55

Manufacturer:	Lecta
Website:	www.adestor.com
Country of manufacture:	Barcelona
Applications:	Suitable for laser and inkjet printing and photocopying machines.

Product components

Facestock (LASER): Uncoated wood free paper guaranteed for laser printing.

Adhesive (RA678): Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces.

Liner (KL55): White liner guaranteed for laser printing. For the conversion of reels to sheets.

Printing techniques: Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, laser.

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

FACESTOCK

Property	Units	Value	Tolerance
Substance	g/m ²	70	± 4%
Thickness	µm	90	± 5
Brightness ISO	%	103	± 2
Opacity	%	91	- 2
Whiteness CIE	%	143	± 5
Tensile strength MD/CD	kN/M	≥ 3.2 / ≥ 1.9	- 2

ADHESIVE

Property	Units	Value	Tolerance
Adhesion (Peel stainless steel 1 week)	N/25mm	1.7	1 - 2.9
Shear (1kg, in ² /glass)	Min	120	≥ 60
Tack (Quick Stick stainless steel)	N	1.2	0.7 – 1.7
Minimum labelling temperature	°C	5	
Minimum service temperature	°C	-20	
Maximum service temperature	°C	80	

LINER

Property	Units	Value	Tolerance
Substance	g/m ²	55	52.5 - 57.5
Thickness	µm	56	52 - 60
Tensile strength MD/CD	kN/M	≥ 3.8 / ≥ 1.6	

Shelf Life: From the date of manufacture 1 year in 20°C and RH 50%

These characteristics are average values supplied for guidance purposes

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.