

PRODUCT

PMC BOPP WHITE GLOSS NTC PP32C WG62

Manufacturer:	PMC Label Materials Co. Ltd
Website:	www.pmlabel.com
Country of manufacture:	Thailand
Applications:	For highly decorative labels on food, cosmetics, toiletries, automotive lubricants and household products where durability and resistance to moisture and chemicals are required. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

Product components

Facestock (WHITE GLOSS):	Gloss white, corona treated, and biaxially polypropylene film. Recommended to re-corona treated before printing. Printers and inks is always recommended prior to use.
Adhesive (PP32C):	General purpose permanent adhesive, with excellent aging resistance. Featuring good tack to low surface energy.
Liner (WG62):	Super calendered White Glassine paper

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.



TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	45.6gsm	58 micron (2.3 mil)
Liner	60gsm	54 micron (2.1 mil)
Total	127.6 gsm, ±10%	133 micron, ±10%

ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.0	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 11.5	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.0	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.