

PRODUCT

PMC FLUORO YELLOW PP33F WG62

Manufacturer:	PMC Label Materials Co. Ltd
Website:	www.pmlabel.com
Country of manufacture:	Thailand
Applications:	Designed for general purpose label for eye catching applications such as instructional, promotional and POS label. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

Product components

Facestock (FLUORO YELLOW):	One sided fluorescent coloured coated paper.
Adhesive (PP33F):	General purpose permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.
Liner (WG62C):	Super calendered White Glassine paper.

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.



TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	72gsm	80 micron (3.1 mil)
Liner	60gsm	54 micron (2.1 mil)
Total	153 gsm, ±10%	154 micron, ±10%

ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.5	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12.0	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.5	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.