

PRODUCT

PMC GLOSS COAT PP30F WG62

Manufacturer: PMC Label Materials Co. Ltd

Website: www.pmlabel.com

Country of manufacture: Thailand

Applications: Designed for high quality multicolor labels and stickers with high flexibility conformity requirements. It is advisable to test the product with end-use conditions during the qualification to ensure it meets specific requirements.

Product components

Facestock (GLOSS COAT): Designed for high quality multicolor labels and stickers with high flexibility conformity.

Adhesive (PP33F): General purpose permanent adhesive, with very good water and aging resistance. Featuring excellent adhesion to low surface energy substrates.

Liner (WG62): Super calendered White Glassine paper.

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.

TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	90gsm	72 micron (2.8 mil)
Liner	60gsm	54 micron (2.1 mil)
Total	171 gsm, ±10%	146 micron, ±10%

ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.5	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12.0	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.5	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

Note: It is recommended that all pressure sensitive materials are trialled prior to printing.