

PRODUCT

---

**PMC PREMIUM GLOSS HI WHITE PP30F WG62**

---

<b>Manufacturer:</b>	PMC Label Materials Co. Ltd
<b>Website:</b>	www.pmlabel.com
<b>Country of manufacture:</b>	Thailand
<b>Applications:</b>	Mainly used for commercial inkjet printing. Universally printable with dye inks. A list of printers showing compatibility with pigmented ink. We recommend checking suitability of this product on your printer before using. It is advisable to test the product with the end-use conditions during the qualification to ensure it meets specific requirements.

**Product components**

---

Facestock (Premium Gloss Hi White):	Super white with gloss surface, one side cast coated and mirror finished printing paper.
Adhesive (PP30F):	General purpose permanent adhesive. Featuring excellent adhesion to low surface energy substrates.
Liner (WG62):	Super-calendered White Glassine paper.

---

B&F Papers has endeavoured to ensure this information; however, we do not accept liability for any error or omission. We reserve the right to update this information without prior notice.



## TECHNICAL SPECIFICATIONS

Property	Grammage	Thickness
Facestock	87gsm	104 micron (4.1 MIL)
Liner	60gsm	55 micron (2.2 MIL)
Total	168 gsm, ±10%	179 micron, ±10%

## ADHESIVE

Property				
Initial Tack	Glass	FTM 9	≥ 12.5	N/25 mm
Initial Tack	Stainless Steel	FTM 9	≥ 12.0	N/25 mm
Adhesion to	Stainless Steel	FTM 2 20 minute 90° peel	≥ 6.5	N/25 mm

Minimum Service Temperature	-40 °C	-40 °F
Maximum Service Temperature	120 °C	248 °F
Minimum Application Temperature	-5 °C	23 °F

Shelf Life: 1 year if stored in 22°C and 50% RH condition. The product must be stored in a shady or cool place and not directly exposed to sunlight. These characteristics are average values supplied for guidance purposes.

**Note: It is recommended that all pressure sensitive materials are trialled prior to printing.**